PAR16 LED SIRIUS-P 220-240V

* COB LED con riflettore: efficienza migliorata del 20% rispetto alla precedente versione Sirius.

* Lampada di dimensioni standard, impiega tecnologia COB ad alta efficienza.

* Incremento delle dimensioni e nuovo disegno del riflettore per un miglior controllo ottico.

* Una lampada potente che consente la sostituzione di una alogena da 75W consentendo un risparmio energetico superiore all'92%.

* Vano in materiale termoconduttore di nuova generazione per l'alloggiamento delle componenti elettroniche: ottimizzazione della dissipazione del calore e maggior sicurezza per l'utente.

* Confezione in scatola di cartone appendibile.

INFORMAZIONI D'UTILIZZO

* Non impiegare con variatore di luce.

* Il codice 38630PD è dimmerabile con dimmers a TRIAC.

Caratteristiche Articolo

Codice Articolo	38640P
Tensione di lampada	220-240 V
Potenza nominale	6 W
Attacco	GU10
Corrente di lampada	0,05 A
Flusso nominale	510 LUMEN
Tonalità della luce	Luce naturale
Temperatura di colore	4000 K
Apertura Fascio	38°
Diametro	50 mm
Lunghezza	57,5 mm
Peso	60 g

Prestazioni

Axis cd	725
Ra	>80
Durata di vita	>25000 h
Classe energetica	A+
kWh/1000h	7
Equivalenza con incandescenza	57 W

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products.

Caratteristiche tecniche

Impiegabile con variatore di intensità luminosa	NO
Fattore di potenza	0,55
Tempo di riscaldamento fino al 60% del rendimento completo	Piena Luce Istantanea
Tempo di innesco	<0,2s
Mercurio espresso in mg	0
LLMMF - Mantenimento del flusso luminoso a fine vita	70
T(°C) ambiente di utilizzo	-25°C / +35°C
Norme e Direttive di riferimento	2011/65/UE * RoHS 2012/19/UE * RAEE 2014/30/UE * Compatibilità Elettromagnetica 2014/35/UE * Bassa Tensione EN 61547 * anno 2010 EN 55015 * anno 2014 EN 61000-3 -2 * anno 2007 (+A1/+A2:2011) EN 61000-3-3 * anno 2014 EN 62471 * anno 2010 IEC/TR 62471-2 EN 62031 * anno 2009 (+A1:2013) EN 62560 * anno 2013 EN 60968 * anno 2013 2010/30/EU * Energy Consumption 874/2012 * Regulation for Energy Labelling 2009/125/CE * Progettazione Eco Compatibile 1194/2012 * Progettazione Eco Compatibile

Informazioni Spedizione

Dimensioni confezione singola L x H x L (mm)	51 x 51 x 65
Barcode Articolo	8011905847944
Imballo	10 pz
Barcode Master	8011905847951

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products.